

Technical Data Sheet

Motor Type: ASGH

Catalogue No: RD00245-56C

Nameplate Information

| | | | | | | |
|-----------|------------|----------------|-------------|-------------|------------|----------------|
| HP | Pole | RPM | Frame | Voltage | Hz | Phase |
| 2 | 4 | 0 | 56C | 575 | 0 | 0 |
| Enclosure | Ins. Class | Service Factor | Time Rating | NEMA Design | Rated Amb. | Rated Altitude |
| ODP | 0 | 0.00 | 0 | 0 | 0 °C | 0 |

Typical Performance

| Efficiency (%) | | | | Power Factor (%) | | |
|-------------------|-----------------------------|---------------------------------|--------------------------------------|---------------------|-----------|--------------------------------|
| Full Load | | 3/4 Load | 1/2 Load | Full Load | 3/4 Load | 1/2 Load |
| Nom. | Min. | | | | | |
| 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Torque | | | | Current (A) | | |
| Full Load (lb-ft) | Locked Rotor (% FLT) | Pull Up (% FLT) | Break Down (% FLT) | No Load | Full Load | Locked Rotor |
| 0.00 | 0 | 0 | 0 | 0.0 | 0.0 | 0 |
| NEMA KVA Code | Inertia (WR ²) | | | Safe Stall Time (s) | | Noise Level Sound Press. dB(A) |
| | Rotor (lb-ft ²) | NEMA Load (lb-ft ²) | Max. Allowable (lb-ft ²) | Cold | Hot | |
| 0 | 0.000 | 0 | 0 | 0 | 0 | 0 |

VFD Duty Information

| Speed Range | | | VFD | | S.F. |
|-----------------|-----------------|----------------|---------|------|------|
| Constant Torque | Variable Torque | Constant Power | Carrier | Type | |
| 0 | 0 | 0 | 0 | 0 | 0 |

Additional Information

| Bearings | | Approx. Weight |
|----------|-----|----------------|
| DE | NDE | lbs |
| 0 | 0 | 0 |

Hazardous Locations Information

| | |
|----------------------------|-------|
| 0 | |
| 0 | |
| 0 | |
| Temp Code (Sinewave / VFD) | 0 / 0 |