



- NOTES:
1. BOX CAN BE ROTATED IN 90° STEPS.
 2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180° THIS MODIFICATION CAN BE PERFORMED ONLY BY MARATHON ELECTRIC OR BY A FACILITY THAT IS COVERED UNDER UNDERWRITERS LABORATORIES INC.PTKQ,TITLED "MOTOR AND GENERATORS, REBUILT FOR USE ININ HAZARDOUS LOCATIONS".

| DASH | FRAME | B | C | BS | 2F | 2FF | 2FFF | AG | NO. | REVISION | BY & DATE | CHK | ANG | FINISH | PREV |
|------|---------|------|-------|------|------|------|------|-------|-----|--|----------------|-----|-------|--------|------|
| | | | | | | | | | 5 | UPDATED DRAWING | TJW 05/04/2007 | | | | |
| | | | | | | | | | 4 | UPDATED THE NOTE. | ST 2/13/2007 | AT | DEC. | INCHES | |
| | | | | | | | | | 3 | REDREW INTO AUTOCAD / CHANGED LOCATION | | | | | |
| | | | | | | | | | 2 | CORRECTED BRACKET AND ADAPTED CN29200-1575 | TJB 03-21-2001 | | .XXX | ±.005 | |
| | | | | | | | | | 1 | NEW DRAWING MU29393 | CAV 03-20-2000 | | .XXXX | ±.0005 | |
| 725 | 213TC | 7.00 | 24.67 | 2.75 | 5.50 | - | - | 21.55 | | | | | | | |
| 875 | 215TC | 8.50 | 26.17 | 3.50 | 7.00 | - | - | 23.05 | | | | | | | |
| 875 | 213/5TC | 8.50 | 26.17 | 3.50 | 7.00 | 5.50 | 5.50 | 23.05 | | | | | | | |
| 1000 | 213TC | 9.75 | 27.42 | 4.12 | 8.25 | 5.50 | 5.50 | 24.30 | | | | | | | |
| 1000 | 215TC | 9.75 | 27.42 | 4.12 | 8.25 | 7.00 | 7.00 | 24.30 | | | | | | | |

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT



TITLE OUTLINE - EPNV
210T FR. - DBL. C'FACE W/BEI ENCODER

| | |
|-------------|----------------|
| DRAWN | CAV 03-16-2000 |
| CHK | ML 03-20-2000 |
| APPD | PH 03-20-2000 |
| SCALE | 1=4 |
| REF | |
| FMF | |
| PREV | |
| CAD FILE | ss88076 |
| SIZE | B |
| DRAWING NO. | SS88076 |
| PAGE | OF |
| REV. | 5 |