



DASH	FRAME	C	B	2F	2FF	BS	AG	MOUNTING	# OF HOLES
575	182TC	23.33	5.50	4.50	-	2.25	12.15	F1 ONLY	4
675	182TC	24.33	6.50	4.50	5.50	2.75	13.15	F1 ONLY	8
675	184TC	24.33	6.50	4.50	5.50	2.75	13.15	F1 OR F2	8
800	184TC	25.58	7.75	5.50	6.75	3.38	14.40	F1 OR F2	8

- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

NO.	REVISION	BY & DATE	CHK	ANG	±1/2'	FINISH	PREV
5	UPDATED DRAWING	RJW 04-24-2007	DEC.	INCHES	UNLESS SPECIFIED		
4	ADD HOLE # CHART/UPDATE LFT. VIEW CN32612	RWR 03/08/2004	.X	±.1			
3	UPDATE ODE SHAFT EXTENSION MU37306	DRS 08/17/2001	ML	.XX	±.03		
2	ADDED ENCODER DIA. MU37306	DAH 07/11/2001	ML	.XXX	±.005		
1	NEW DRAWING MU37306	DAH 07/10/2001	ML	.XXXX	±.0005	MAT'L	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT							
RFP						CAD FILE ss69132	SIZE B
DIST LB						DRAWING NO. SS69132	PAGE 1 OF 1 REV. 5