



UNITS: INCHES

FRAME SIZE	MOTOR DIMENSIONS											CONDUIT BOX						
	A	B	C	D	G	J	K	M	O	P	T	AA[NPT]	AB	AC	AE	AF	XL	XN
445T/447T	21.9	22.9	52.2	11.00	1.1	4.3	4.8	19.3	22.0	22.4	3.6	3.00	21.5	16.4	11.00	8.7	15.7	11.5
445TZ/447TZ	21.9	22.9	53.9	11.00	1.1	4.3	4.8	19.3	22.0	22.4	3.6	3.00	21.5	16.4	11.00	8.7	15.7	11.5
FRAME SIZE	MOUNTING			SHAFT EXTENSION		KEY SEAT		BEARINGS		MAXIMUM WEIGHT								
445T/447T	E	2F	H	BA	N-W	V	U	R	S	ES	LS	OS						
445TZ/447TZ	9.00	16.5/20.00	0.86	7.50	8.50	8.25	3.375	2.880	0.875	6.91	NU318C3	6318C3	2320	lbs.				
	9.00	16.5/20.00	0.86	7.50	10.125	9.875	3.375	2.880	0.875	8.50	NU318C3	6318C3	2320	lbs.				

TAG NO's:

CUSTOMER: _____ MOTOR MODEL NO.: _____

P.O. NO.: _____ HP: _____ VOLTAGE: _____ RPM(SYN): _____ Hz: _____

FRAME SIZE: _____ PRODUCT TYPE: IEFEC EGP III, EPACK, & HIGH EFFICIENCY

COMMENTS: _____

PER: _____ DATE: _____

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED CERTIFIED

- STANDARD (NO AUX. BOXES)
- RTD AUX. BOX
- SPACE HEATER AUX. BOX
- BEARING RTD's

- NOTES:
- DIMENSION V REPRESENTS LENGTH OF STRAIGHT PART OF SHAFT
 - MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
 - KEY DIMENSIONS EQUAL S x S x 6.91 FOR "T" AND S x S x 8.50 FOR "TZ" (MOTOR SUPPLIED WITH KEY)
 - MOTOR WEIGHT SHOWN IS MAXIMUM HORSEPOWER IN FRAME
 - STANDARD PRODUCT USE BI-DIRECTIONAL FAN, OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.
 - DIMENSIONS FOR 445T MOUNTING EQUALS 2F LOCATED IN 445T/447T

TOSHIBA

TOSHIBA INTERNATIONAL CORPORATION

TOTALLY-ENCLOSED FAN-COOLED
HORIZONTAL FOOT-MOUNTED
3 PHASE INDUCTION MOTOR
F1 ASSEMBLY

XT SERIES

VISIT OUR WEBSITE AT:
www.toshiba.com/ind