



UNITS: INCHES

| FRAME SIZE | MOTOR DIMENSIONS |             |      |                 |       |       |          |       |       |          |         | CONDUIT BOX    |           |      |      |     |      |      |
|------------|------------------|-------------|------|-----------------|-------|-------|----------|-------|-------|----------|---------|----------------|-----------|------|------|-----|------|------|
|            | A                | B           | C    | D               | G     | J     | K        | M     | O     | P        | T       | MAXIMUM        | AB        | AC   | AE   | AF  | XL   | XN   |
| 5810USS    | 28.0             | 42.2        | 72.5 | 14.50           | 1.6   | 6.3   | 9.3      | 27.6  | 30.5  | 31.6     | 5.1     | 4.00           | 31.1      | 23.8 | 14.5 | 9.3 | 23.4 | 14.2 |
| 5810US     | 28.0             | 42.2        | 72.3 | 14.50           | 1.6   | 6.3   | 9.3      | 27.6  | 30.5  | 31.6     | 5.1     | 4.00           | 31.1      | 23.8 | 14.5 | 9.3 | 23.4 | 14.2 |
| 5810UZ     | 28.0             | 42.2        | 77.6 | 14.50           | 1.6   | 6.3   | 9.3      | 27.6  | 30.5  | 31.6     | 5.1     | 4.00           | 31.1      | 23.8 | 14.5 | 9.3 | 23.4 | 14.2 |
| FRAME SIZE | MOUNTING         |             |      | SHAFT EXTENSION |       |       | KEY SEAT |       |       | BEARINGS |         | MAXIMUM WEIGHT |           |      |      |     |      |      |
|            | E                | 2F          | H    | BA              | N-W   | V     | U        | R     | S     | ES       | LS      |                | OS        |      |      |     |      |      |
| 5810USS    | 11.50            | 36.00/32.00 | 1.2  | 10.00           | 6.75  | 6.50  | 2.375    | 2.021 | 0.625 | 5.00     | 63J3C3  | NU313C3        | 7800 lbs. |      |      |     |      |      |
| 5810US     | 11.50            | 36.00/32.00 | 1.2  | 10.00           | 6.25  | 6.19  | 3.625    | 3.134 | 0.875 | 5.00     | 63J20C3 | 6320C3         | 7800 lbs. |      |      |     |      |      |
| 5810UZ     | 11.50            | 36.00/32.00 | 1.2  | 10.00           | 11.62 | 11.38 | 5.250    | 4.550 | 1.250 | 10.00    | NU328C3 | 6320C3         | 7800 lbs. |      |      |     |      |      |

CUSTOMER: \_\_\_\_\_ MOTOR MODEL NO.: \_\_\_\_\_ TAG NO's: \_\_\_\_\_

P.O. NO.: \_\_\_\_\_ HP: \_\_\_\_\_ VOLTAGE: \_\_\_\_\_ RPM(SYN.): \_\_\_\_\_ HZ: \_\_\_\_\_  
 FRAME SIZE: \_\_\_\_\_ PRODUCT TYPE: IEFEC EGP III, EPACT, & HIGH EFFICIENCY QUARRY DUTY  
 COMMENTS: \_\_\_\_\_

PER: \_\_\_\_\_ DATE: \_\_\_\_\_

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE  PRELIMINARY  
 DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED  CERTIFIED

- NOTES:
- DIMENSION V REPRESENTS LENGTH OF STRAIGHT PART OF SHAFT
  - MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
  - KEY DIMENSIONS EQUAL S x S x 10.00 FOR UZ AND S x S x 5.00 FOR USS & US (MOTOR SUPPLIED WITH KEY)
  - MOTOR WEIGHT SHOWN IS MAXIMUM HORSEPOWER IN FRAME
  - THIS DIMENSION EQUALS 2F FOR 5809USS/US/UZ MOUNTING
  - STANDARD PRODUCT USE BI-DIRECTIONAL FAN, OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE

STANDARD (NO AUX. BOXES)  
 RTD AUX. BOX  
 SPACE HEATER AUX. BOX  
 BEARING RTD's

**TOSHIBA**  
 TOSHIBA INTERNATIONAL CORPORATION

TOTALLY-ENCLOSED FAN-COOLED  
 HORIZONTAL FOOT-MOUNTED  
 3 PHASE INDUCTION MOTOR  
 F1 ASSEMBLY

**XT SERIES**  
 VISIT OUR WEBSITE AT:  
 www.toshiba.com/ind