



DASH	FRAME	C	XB	BS	DASH	FRAME	C	XB	BS
656	56-65	11.22	0	3.18	856	56-85	13.22	5.00	5.18
706	"-70	11.72	0	3.68	906	"-90	13.72	5.00	5.68
756	"-75	12.22	5.00	4.18					
806	"-80	12.72	5.00	4.68					

* DIMENSION IS FROM RESILIENT RING END CAP TO END OF SHAFT
 NOTE:
 1. MOTOR MUST BE ROTATED TO .75" STRIP SOCKET CLEARANCE FOR GROUND SCREW, MAXIMUM (10 DEGREES).

				TOLERANCES UNLESS SPECIFIED			DRAWN SMC 02-17-1992						
				DEC.	INCHES		CHK	ET 02-17-1992					
4	UPDATED DRAWING			RJW	03-28-2007	.X	±.1	APPD	MJ 02-17-1992				
3	REDRAWN IN AUTOCAD			TAT	09-01-2004	ML	.XX	±.03	SCALE	3=8			
2	ADDED NOTE			PGK	06-11-1997		.XXX	±.005	REF				
1	NEW DRAWING			SMC	02-17-1992		.XXXX	±.0005	FMF				
NO.	REVISION			BY & DATE		CHK	ANG	±'30"	FINISH	PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP		CAD FILE 100573			SIZE	DRAWING NO.	PAGE	OF	REV.
				DIST	WP				A	100573			4