

# Product Information Packet

November 8, 2016

Data shown is for the current revision model #. Ensure your nameplate model # matches.

<b>Model Number:</b>	<b>5KS444XAA366D</b>
<b>Catalog Number:</b>	<b>M9357</b>
<b>Instruction Manual:</b>	GEI-56128
<b>Connection Diagram:</b>	GEM2034E-FIG7
<b>Outline Drawing:</b>	239C6600ZA

Accessory Connection Diagrams			
<b>Bearing Thermocouple:</b>	None	<b>Heater:</b>	None
<b>RTD:</b>	None	<b>Thermistor:</b>	None
<b>Thermostat:</b>	None	<b>Winding Thermocouple:</b>	None
<b>Bearing RTD:</b>	None		

## Table of Contents

Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04
Spare parts	05



**Marks:**

<b>MODEL NUMBER:</b>	<b>5KS444XAA366D</b>	<b>Estimated Weight:</b>	1880 Lbs
<b>Outline Drawing:</b>	239C6600ZA	<b>Time Rating:</b>	CONT
<b>Connection Diagram:</b>	GEM2034E-FIG7	<b>Enclosure:</b>	TEFC
<b>Instruction Book:</b>	GEI-56128	<b>Encl Construction:</b>	841
<b>Design Code:</b>	44BD3081A	<b>Ambient Max(°C):</b>	40
<b>Type:</b>	KS	<b>Alt Ambient Max(°C):</b>	--
<b>Frame:</b>	444T	<b>Insulation Class:</b>	H
<b>Phases:</b>	3	<b>NEMA Design:</b>	B
<b>Poles:</b>	6	<b>Nominal Efficiency:</b>	95.0 %
<b>Output Power:</b>	100HP 74KW	<b>Guaranteed Efficiency:</b>	94.5
<b>RPM:</b>	1190	<b>3/4 Load Efficiency:</b>	95.1
<b>Voltage:</b>	460	<b>KVA Code:</b>	G
<b>Hertz:</b>	60	<b>Max KVAR:</b>	35.7
<b>Amps - FL:</b>	122.0	<b>Power Factor:</b>	81.0
<b>Service Factor:</b>	1.15	<b>Bearing - DE:</b>	NU 318
<b>Alt Service Factor:</b>	--	<b>Bearing - ODE:</b>	6318ZC3

**Enclosure is Totally Enclosed Fan-Cooled**

**Stamped Nameplate Notes:**

IEEE-STD-841-2009  
 ROLLER BEARING - FOR BELTED LOAD ONLY  
 DE BRG 90RU03M, ODE BRG 90BC03JP3  
 STAMP NP249A5564P051 AS BELOW:  
 MODEL:5KS444XAA366D S/N: XXX  
 CSA CERTIFIED CSA09.2216219 FOR EX NA IIC 200 C GC  
 CL 1 ZONE2 AEX NA IIC 200C;CL 1 DIV2 GRP ABCD 200C  
 IN -25C <= AMB <= 40C, 1.0 SF ON SINE-WAVE PWR  
 SURF TEMP 200C AT 1.15SF ON SINE-WAVE PWR  
 OR 200C VT OR 230C CT OR 200C CHP PWM CONTROL  
 ALTERNATE RATING FOR PWM CONTROL 1.0SF 40C AMB  
 VT 0 - 60 HZ, CT 6-60 HZ, CHP 60-90 HZ.

**Additional Information:**

6P - T EXTN  
 PAINTED FRAME ID & SHAFT,  
 FAN COVER INSIDE & ODE E/S OUTSIDE  
 700 CU IN - 3.00" NPT  
 INPRO SEAL BOTH ENDS  
 OIL RESISTANT SLEEVING ON LEADS  
 .002" TIR SHAFT RUNOUT  
 ROUTINE TEST REPORT AND 5 POINT VIBRATION TEST  
 REPORT INCLUDED IN C/B  
 COPPER WASHER UNDER HEADS OF BEARING CAP BOLTS,  
 APPLY TITE-SEAL (A50CD427A) ON BEARING CAP SCREWS,  
 RABBETS AND PLUG THREADS.  
 B5F4C4 HIGH FATIGUE STEEL AISI 4142 SHAFT MATERIAL



GROUND PAD  
F1 MOUNTING

**Performance Characteristics**

1st Winding 1st Connection

**Design: 44BD3081A**

**Marks:**


LOAD %	125.0	115.0	100.0	75.0	50.0	25.0	0.0
% EFF	94.38	94.61	95.09	95.09	94.65	91.92	0.00
% PF	83.04	82.54	81.21	76.66	66.5	44.2	3.53
AMPS	149.27	137.83	121.2	96.29	74.35	57.58	49.86

<b>TORQ(FL)#FT</b>	440.81	<b>TORQ(LR)%FL</b>	180.49	<b>TORQ(BD)%FL</b>	245.77
<b>AMPS(LR)</b>	712.54	<b>PF AT START</b>	0.34		


This motor is capable of two cold or one hot start with a maximum connected load inertia of 5267 Lb-Ft Sq (221.74 Kg-meter Sq)at 100% voltage, where the load torque varies with the square of the speed. Acceleration time with maximum inertia and the above load type is 42 seconds. Safe stall time at 100% voltage is 83 seconds cold, 51 seconds hot. Rotor inertia is 78.74 Lb-Ft Sq (3.31 Kg-meter Sq).

<b>Open Circuit A-C:</b>	0.821	<b>Short Circuit D-C:</b>	0.025
<b>Short Circuit A-C:</b>	0.052	<b>X/R Ratio:</b>	9.32
<b>Stator Slots:</b>	72	<b>Rotor Slots:</b>	58

**Speed Torque Current Curve (First Connection, First Speed)**



Marks:



REV.	DESCRIPTION	DATE	APPROVED


1. CONDUIT BOX MAY BE PLACED WITH THE ENTRANCE DOWN, UP OR ON EITHER.

2. F-1 ASSEMBLY AS SHOWN.

3. F-2 ASSEMBLY CONDUIT BOX ON OPPOSITE SIDE.

4. BRACKETED DIMENSIONS ARE METRIC (MILLIMETERS).

5. TOLERANCE ON PERMISSIBLE SHAFT EXTENSION MINIMUM IS .002 T.I.R.



MODEL	TEASMI	DATE	01/21/15
SCALE	TEASMI	DATE	01/21/15
DESIGN	HAREBHAN	DATE	01/21/15
DATE	HAREBHAN	DATE	01/21/15
SCALE	TEASMI	DATE	01/21/15
SCALE	0.200	REF. NO.	239C66002A
SCALE	0.200	REF. NO.	239C66002A
SCALE	0.200	REF. NO.	239C66002A

**GENERAL ELECTRIC COMPANY**

**OUTLINE**

**444/445 T TFFC XSD 841**

**700 CU. IN. CONDUIT BOX**

**239C66002A**

**0**

DISTRIBUTION: MMP

Marks:

**Connection Diagram**  
**GEM2034E-FIG7**



End shield Assembly		
Part Description	DE Side Part#	ODE Side Part#
End Shield	115E4355AA1	115E4355LL1
Bearing	235A2519AA01	235A2514AG01
Slinger/Inproseal	235A4575GS5	235A4575GS5

Fan & Fan Cover Assembly	
Part Description	Part#
Fan	159C7100G03
Fan Cover	128D6841AA1

Conduit & Accessories Box Assembly	
Part Description	Part#
Conduit Box	118D4408AD2

Mechanical Accessories	
Part Description	Part#
Brake	
Tachometer	