



UNITS: INCHES		NOTES: 1. MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS 2. STANDARD PRODUCT USES BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE. 3. KEY DIMENSIONS EQUAL 0.312"x 0.312"x 2.38" (MOTOR SUPPLIED WITH KEY)
ROTATION FROM NDE		
<div><div><div></div></div><div>X</div></div> CCW	<div><div><div></div></div><div></div></div> CW	

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE ☐ PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED ☒ CERTIFIED

<b>TOSHIBA</b> <a href="http://www.toshiba.com/tic">www.toshiba.com/tic</a> <b>TOSHIBA INTERNATIONAL CORPORATION</b>	<b>SEVERE DUTY</b> <b>EQP Global SD</b>	<b>TOTALLY ENCLOSED FAN COOLED</b> <b>ROUND BODY C-FACED</b> <b>3 PHASE INDUCTION MOTOR</b> <b>213TC-215TC F1 ASSEMBLY</b>	<b>DRAWING #:</b> MDSL205-03 <b>REV. DATE:</b> 06/27/18 <b>REV. #:</b> 3 <b>PER.:</b> M. O'DOWD <b>REV. DESCRIP.:</b>