



UNITS: INCHES

BEARINGS		APPROX. WEIGHT
LS	OS	
6314ZZC3	6312ZZC3	893 lbs

- NOTES:  
 1. MAIN CONDUIT BOX MAY BE ROTATED IN 90 INCREMENTS  
 2. STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.  
 3. KEY DIMENSIONS EQUAL (MOTOR SUPPLIED WITH KEY)
- 0.625" x 0.625" x 4.25"

CUSTOMER: _____	MOTOR MODEL NO.: _____	TAG NUMBERS _____ _____ _____ _____	<input checked="" type="checkbox"/> STANDARD (NO AUX. BOXES)
P.O. NO.: _____	HP: _____ VOLTAGE: _____ RPM(SYN.): _____ HZ: _____		<input type="checkbox"/> RTD AUX. BOX
FRAME SIZE: 360T	PRODUCT TYPE: COOLING TOWER		<input type="checkbox"/> SPACE HEATER AUX. BOX
COMMENTS: _____	_____		<input type="checkbox"/> BEARING RTD's
PER: _____	DATE: _____		

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE  PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED  CERTIFIED

**TOSHIBA**  
 TOSHIBA INTERNATIONAL CORPORATION

MDSLV503-07  
 TOTALLY ENCLOSED FAN COOLED  
 3 PHASE INDUCTION MOTOR  
 F1 ASSEMBLY

SEVERE DUTY  
**EQP Global CT**  
**XT SERIES**  
 www.toshiba.com/ind