



DASH	FRAME	C	XB	DASH	FRAME	C	XB
756	56-75	12.22	5.00	906	56-90	13.72	5.00
806	56-80	12.72	5.00	956	56-95	14.22	5.00
856	56-85	13.22	5.00	1006	56-106	14.72	5.00

*DIMENSION IS FROM RESILIENT RING END CAP TO END OF SHAFT

NOTES:

- MOTOR MUST BE ROTATED TO PROVIDE SOCKET CLEARANCE FOR GROUND SCREW, MAXIMUM (10 DEGREES).

NO.	REVISION	BY & DATE	CHK	TOLERANCES UNLESS SPECIFIED	
				DEC.	INCHES
4	REDRAWN IN AUTOCAD	TAT 09-01-2004	ML	.XX	±.03
3	ADDED DASH 1006	CN 27492 BLR 02-19-1999		.XXX	±.005
2	REDRAWN ON CADD AND ADDED NOTE	CN 24378 PGK 06-12-1997		.XXXX	±.0005
				ANG	±7'30"

	DRAWN PGK 06-06-1997	
	CHK ML 06-09-1997	
	APPD GK 06-09-1997	
TITLE OUTLINE	SCALE 3=8	
56 FR. - DR.PR. - RESIL. MT.	REF	
MAT'L.	FMF	
FINISH	PREV	

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT

RFP	CAD FILE 100218	SIZE A	DRAWING NO. 100218	PAGE OF	REV. 4
DIST WP					