



DASH NO.	"C"	"AD"
650	19.01	6.01
700	18.51	6.51
750	19.01	7.01
800	19.51	7.51
850	20.01	8.01

MAXIMUM FACE RUNOUT TO BE .004 TIR  
 MAXIMUM PILOT ECCENTRICITY .004 TIR  
 PERMISSIBLE SHAFT RUNOUT .002 TIR

**WASHGUARD FEATURES:**

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE
- 4) GASKETS THROUGHOUT

NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	TOLERANCES UNLESS SPECIFIED	DEC.	INCHES	TITLE	DRAWN					
											RDW	1/14/04				
02	ADDED PLASTIC PLUG NOTE PER ISAAC 08-1811	ARV 5/1/08	.X		±.1					LEESON ELECTRIC MOTORS GEARMOTORS AND DRIVES	CHK	SW 1/14/04				
01	ADDED 1/2-14 NPT HOLE AT 9 O'CLOCK IN CONDUIT BOX, AND ADDED 1/2-14 PIPE PLUG, PER ECR 83722	BJB 02/04/04	.XX		±.03					OUTLINE - 140TC FRAME TEFC - "C" FACE	SCALE	1-2				
			.XXX		±.005					WASHGUARD BRAKE MOTOR	REF	028571				
			.XXXX		±.0005						FMF	121615				
											PREV					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT										RFP	1/14/04	CAD FILE	028574	SIZE	DRAWING NO.	REV.
										DIST			B	028574	02	