

### Technical Data Sheet

Motor Type: BEGCFD

Catalogue No: FD0/34

#### Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
0.33	4	1770	56	115 / 230	60	1
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous		-40 to 40 °C	<3300 ft

#### Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
51.0				47.0		
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
0.14	425		400		8.5 / 4.3	44.00 / 22.00
NEMA KVA Code	Inertia (WR <sup>2</sup> )			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft <sup>2</sup> )	NEMA Load (lb-ft <sup>2</sup> )	Max. Allowable (lb-ft <sup>2</sup> )	Cold	Hot	
	0.066					

#### VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	

#### Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6205ZZ	6203ZZ	32

#### Hazardous Locations Information

Temp Code (Sinewave / VFD)	/
----------------------------	---