



DASH NO.	"C"	"AD"
500	14.00	2.44
550	14.50	2.94
600	15.00	3.44
650	15.50	3.94
700	16.00	4.44

MAXIMUM FACE RUNOUT TO BE .004 TIR
 MAXIMUM PILOT ECCENTRICITY .004 TIR
 PERMISSIBLE SHAFT RUNOUT .002 TIR

WASHGUARD FEATURES:

- 1) SHAFT SEAL & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE
- 4) GASKETS THROUGHOUT

NO.	REVISION	BY & DATE	CHK	ANG	TOLERANCES UNLESS SPECIFIED		MATERIAL	FINISH	DRAWN	RDW	REV.
					DEC.	INCHES					
02	ADDED DRAIN SCREWS PER ECR-0034519	ARV 8/8/13	SK	.X	±.1	TITLE	OUTLINE - 56HC FRAME TENV - RIGID "C"	DRAWN	RDW	1/12/03	REV.
01	REV'D DRAIN HOLE SCREW LOC'NS IN L.E ENDBELL TO MATCH ENDBELL MACHINING	BJB 03/18/04	.XX	±.03	SCALE						
			.XXX	±.005	REF	PRO20609					
			.XXXX	±.0005	FMF	116469					
				±1/2'	PREV						
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					RFP	1/12/03	CAD FILE	028572	SIZE	DRAWING NO.	REV.
					DIST				B	028572	02



ELECTRIC MOTORS
GEARMOTORS
AND DRIVES