



UNITS: INCHES

BEARINGS		APPROX. WEIGHT
LS	OS	
6312ZZC3	6312ZZC3	651 lbs

- NOTES:
1. MAIN CONDUIT BOX MAY BE ROTATED IN 90 INCREMENTS
 2. STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.
 3. KEY DIMENSIONS EQUAL 0.500" x 0.500" x 3.88"

<p>CUSTOMER: _____ MOTOR MODEL NO.: _____</p> <p>P.O. NO.: _____ HP: _____ VOLTAGE: _____ RPM(SYN.): _____ HZ: _____</p> <p>FRAME SIZE: 320T PRODUCT TYPE: COOLING TOWER</p> <p>COMMENTS: _____</p> <p>PER: _____ DATE: _____</p>	<p>TAG NUMBERS</p> <p>_____</p> <p>_____</p> <p>_____</p> <p>_____</p>	<p><input checked="" type="checkbox"/> STANDARD (NO AUX. BOXES)</p> <p><input type="checkbox"/> RTD AUX. BOX</p> <p><input type="checkbox"/> SPACE HEATER AUX. BOX</p> <p><input type="checkbox"/> BEARING RTD's</p>
---	--	--

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED CERTIFIED



MDSL503-06
 TOTALLY ENCLOSED FAN COOLED
 3 PHASE INDUCTION MOTOR
 F1 ASSEMBLY

