



- NOTES:  
 1- CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2- CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°  
 3- NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

				TOLERANCES UNLESS SPECIFIED			DRAWN	DRS 06-23-2000		
NO	REVISION	BY & DATE	CHK	ANG	FINISH		CHK	ML 06-26-2000		
5	REVISED MOUNTING HOLE QUANTITY CN 40694	DRS 10-25-2008	ML	DEC	INCHES	TITLE OUTLINE - TEFC - TFPA 280TS FR. - STD - 11.00 LAM	APPR	SW 07-10-2000		
4	REDRAWN IN AUTOCAD	TAT 06-29-2004	ML	X	±.1		SCALE	1:4		
3	CORRECTED C'BOX HOLE NOTE CN 29200-1454	HLB 02-16-2007		.XX	±.03		REF			
2	REMOVED DUAL DRILLING FROM FEET CN 29200-991	NJS 10-26-2000		.XXX	±.005		FMF			
1	NEW DRAWING	DRS 07-10-2000		.XXX	±.0005		PREV	SS200047		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT		RFP				CAD FILE	SS311036	SIZE	DRAWING NO	REV
		DIST	LB					<b>B</b>	<b>SS311036</b>	<b>5</b>

DASH	FRAME	B	C	2F	2FF	BS
1275	284TS	11.50	24.89	9.50		4.75
1425	284/6TS	13.00	26.39	9.50	11.00	5.50