



**NOTES:**

1. ROTATION: RED POSITIVE CCWSE; REVERSIBLE
2. LEADS: 14 AWG
3. END PLAY: .005-.030
4. HIPOT: 1250 VAC FOR ONE SECOND, BOTH LEADS TO CASE
5. VOLTAGE: 12 VDC
6. INSULATION: CLASS F 155°C
7. BEARING SYSTEM: SLEEVE BOTH ENDS
8. LOAD POINT: 60 ozin @ 2900-3200 RPM
9. RUST PROOF SHAFT & KEY DUE TO STORAGE.

				TOLERANCES UNLESS OTHERWISE SPECIFIED		<b>LEESON</b> LEESON ELECTRIC CORPORATION		
				DECIMALS		TRU-TORO DIVISION 201 N. MISSOURI AVE. SEDALIA, MO 65301 U.S.A. ELECTRIC MOTORS, GEARMOTORS AND DRIVES		
				.00	±.01	DRAWN AD 11/1/00	TITLE	
				.000	±.005	CHK'D.	OUTLINE	
000	RELEASE	1639	AD	11/1/00	.0000	±.0005	APPR.	MATL. &/or CUST.
REV	DISCRIPTION	ECRN	BY	DATE	FRACTIONAL	±1/64	SCALE 1 : 1	12 VDC
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED					ANGLES	±1/2°	P/C	SIZE
					INCH/MM	M/F	B	DRAWING NO. 970.6200L