

Product Information Packet

January 12, 2017

Data shown is for the current revision model #. Ensure your nameplate model # matches.

Model Number:	5KS511SAA2007A
Catalog Number:	Q5010
Instruction Manual:	GEI-56128
Connection Diagram:	GEM2034E-FIG20
Outline Drawing:	239C6B00ML

Accessory Connection Diagrams			
Bearing Thermocouple:	None	Heater:	3027JE-1C
RTD:	None	Thermistor:	None
Thermostat:	None	Winding Thermocouple:	None
Bearing RTD:	None		

Table of Contents	
Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04



Marks:

MODEL NUMBER:	5KS511SAA2007A	Estimated Weight:	5567 Lbs
Outline Drawing:	239C6B00ML	Time Rating:	CONT
Connection Diagram:	GEM2034E-FIG20	Enclosure:	TEFC
Instruction Book:	GEI-56128	Encl Construction:	SD
Design Code:	50BD1170B	Ambient Max(°C):	40
Type:	KS	Alt Ambient Max(°C):	--
Frame:	5011L	Insulation Class:	F
Phases:	3	NEMA Design:	B
Poles:	4	Nominal Efficiency:	96.2 %
Output Power:	500HP 370KW	Guaranteed Efficiency:	95.4
RPM:	1785	3/4 Load Efficiency:	96.7
Voltage:	575	KVA Code:	G
Hertz:	60	Max KVAR:	84.1
Amps - FL:	430.0	Power Factor:	90.5
Service Factor:	1.15	Bearing - DE:	NU 320
Alt Service Factor:	--	Bearing - ODE:	6315ZC3

Enclosure is Totally Enclosed Fan-Cooled

Stamped Nameplate Notes:

HTR LDS HE1-HE2 115V 350W
 INVERTER DUTY PER NEMA MG1 PART 31
 ALTERNATE RATING FOR PWM CONTROL:1.0SF 40C AMBIENT
 VAR TORQUE RANGE 0-60 HZ
 ROLLER BEARING - FOR BELTED LOAD ONLY

Additional Information:

4P - L EXTN - SPLIT LEAD
 2500 CU IN - 2(4.00" NPT)
 C/B GRD PLATE
 B5F4C4 HIGH STRENGTH STEEL AISI 4142 SHAFT MATERIAL
 115V HTR LDS TO AUX BOX OPP MAIN CONDUIT BOX
 SPACE HEATER CAUTION NAMEPLATE
 NEMA TYPE GRD PAD
 F1 MOUNTING
 SHAFT BLOCKING FOR SHIPMENT
 PROVISION FOR BTD ON BOTH ENDS PLUGGED

Performance Characteristics

1st Winding 1st Connection

Design: 50BD1170B

Marks:


LOAD %	125.0	115.0	100.0	75.0	50.0	25.0	0.0
% EFF	95.91	96.13	96.6	96.68	96.58	95.13	0.00
% PF	89.97	90.26	90.39	89.48	85.45	69.73	4.35
AMPS	542.31	496.23	429.09	324.56	226.82	141.09	93.81

TORQ(FL)#FT	1472.38	TORQ(LR)%FL	103.81	TORQ(BD)%FL	238.15
AMPS(LR)	2427.11	PF AT START	0.24		


This motor is capable of two cold or one hot start with a maximum connected load inertia of 10824 Lb-Ft Sq (455.69 Kg-meter Sq)at 100% voltage, where the load torque varies with the square of the speed. Acceleration time with maximum inertia and the above load type is 46 seconds. Safe stall time at 100% voltage is 93 seconds cold, 55 seconds hot. Rotor inertia is 192.88 Lb-Ft Sq (8.12 Kg-meter Sq).

Open Circuit A-C:	1.291	Short Circuit D-C:	0.041
Short Circuit A-C:	0.045	X/R Ratio:	15.507
Stator Slots:	72	Rotor Slots:	58

Speed Torque Current Curve (First Connection, First Speed)



Marks:



REV.	DESCRIPTION	DATE	APPROVED


SIGNATURES	DATE
HAERHAN	01/10/15
HAERHAN	01/10/15
HAERHAN	01/10/15
HAERHAN	01/10/15
HAERHAN	01/10/15

ALL DIMENSIONS ARE IN INCHES

THIRD ANGLE PROJECTION

Marks:

Connection Diagram
GEM2034E-FIG20



Heater Connection
3027JE-1C

