



- NOTES:
- CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 - CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 - NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.
 - DIMENSION IN [] DESIGNATE MILLIMETERS.

DASH	FRAME	B	C	2F	BS
2438	447T	22.50 [571.50]	43.29 [1099.57]	20.00 [508.00]	10.00 [254.00]
2938	449T	27.50 [698.50]	48.29 [1226.57]	25.00 [635.00]	12.50 [317.50]

DRAWING REVISION C	REVISION BY JJB	DATE 03-06-2015
ECO ECO-0073041	APPROVED BY JHA	DATE 03-06-2015
ECO DESCRIPTION UPDATED TO CURRENT STANDARDS		
<small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small>		

TOLERANCES UNLESS OTHERWISE SPECIFIED:			
DEC.	INCH.	mm	ANGLE
.X	±0.1	[±2.5]	±0.5°
.XX	±0.01	[±0.25]	
.XXX	±0.005	[±0.127]	
.XXXX	±0.0005	[±0.0127]	
REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [0.076/.381] X 45°			
CORNER FILLETS: R.02 [51]			
MACHINED SURFACES: 125 INCH 3.2 mm SHOWN IN [BRACKETS]			

DRAWN BY JL	Regal Beloit America, Inc.	
DATE 06-24-1992	DESCRIPTION OUTLINE 447/449T FR. - DR. PR.	
APPROVED BY JPN	MATERIAL	PROCESS/FINISH
DATE 07-10-1992		
REFERENCE		
THIRD ANGLE PROJECTION	SIZE B	DRAWING NUMBER SS514258
		SHEET 1 OF 1