



TERM.  
END

NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
2. CONDUIT BOX CAN BE MOUNTED IN OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °. THIS MODIFICATION CAN BE PERFORMED ONLY BY THE ORIGINAL EQUIPMENT MANUFACTURER, OR BY A FACILITY THAT IS COVERED UNDER UNDERWRITERS LABORATORIES INC. CATEGORY PTKQ, TITLED "MOTOR AND GENERATORS, REBUILT FOR USE IN HAZARDOUS LOCATION".
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1212	213/215	22.63	11.76	10	7	5
912	213/215	19.63	8.63	7	5.5	3.5
DASH	FRAME	C	B	2F	2FF	BS

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN SK 10/28/2009	
		DEC INCHES				CHK SK 10/28/2009	
		.X ±.1		TITLE OUTLINE		APPR	
02 UPDATED PER IS12-0462		GR 2/15/2012		PN .XXX ±.005		SCALE 1:8	
01 ADDED F2 MOUNTING VIEW		PN 12/30/2010		SR .XXXX ±.0005		REF SS84370	
NO REVISION		BY & DATE		FINISH		FMF 215TTGN4026	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT		CHK ANG ±730°		CAD FILE 037660		PREV	
		RFP		DIST LB - MT2		SIZE DRAWING NO	
				B		037660	
						REV 02	