



NOTE: 256T HAS 6 MTG. HOLES, USING BOTH 254T AND 256T "2F" LOCATIONS.

FRAME	"C"	"BV"	"B"
254T	20.94	8.23	10.25
256T	22.60	9.06	12.00

		TOLERANCES UNLESS SPECIFIED		<b>LEESON</b>	ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN	DRZ 05/23/01
		DEC.	INCHES			CHK	
		.X	±.1	TITLE		SCALE	3-8
		.XX	±.03	ODP, RIGID MOUNT, NEW CON-BOX		REF	
		.XXX	±.005	MAT'L		FMF	
		.XXXX	±.0005	CAST IRON		PREV	
A	REVISED TO NEW BORDER FORMAT	DWF	12/14/01	CHK	ANG	±1/2"	FINISH
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	DrawingB	SIZE
				DIST			DRAWING NO.
							B
							169551-60
							REV.
							A

ERROR: undefined  
OFFENDING COMMAND: fora

STACK:

```
{dup type /operator type eq { [ exch ] cvx def } { pop pop } ifelse }  
-dictionary-  
-dictionary-  
/Pscript_WinNT_Compat  
-dictionary-
```