



UNITS: INCHES

BEARINGS		APPROX. WEIGHT
LS	OS	
6312ZZC3	6312ZZC3	651 lbs

- NOTES:
1. MAIN CONDUIT BOX MAY BE ROTATED IN 90 INCREMENTS
  2. STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.
  3. KEY DIMENSIONS EQUAL (MOTOR SUPPLIED WITH KEY)
- 0.500" x 0.500" x 3.88"

CUSTOMER: _____	MOTOR MODEL NO.: _____	TAG NUMBERS _____ _____ _____ _____	<input checked="" type="checkbox"/> STANDARD (NO AUX. BOXES)
P.O. NO.: _____ HP: _____ VOLTAGE: _____ RPM(SYN.): _____ HZ: _____			<input type="checkbox"/> RTD AUX. BOX
FRAME SIZE: 320T PRODUCT TYPE: COOLING TOWER			<input type="checkbox"/> SPACE HEATER AUX. BOX
COMMENTS: _____			<input type="checkbox"/> BEARING RTD's
PER: _____ DATE: _____			

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE  PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED  CERTIFIED



MDSL503-06  
TOTALLY ENCLOSED FAN COOLED  
3 PHASE INDUCTION MOTOR  
F1 ASSEMBLY

