



- NOTES:
 1) MAXIMUM FACE RUNOUT .004 T.I.R.
 2) MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 3) PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
 4) GASKETS THROUGHOUT.

109102.00	13.82	11.76	5.85	48	1	1800
109101.00	13.82	11.76	5.85	36	1	1800
108605.00	12.82	10.76	4.85	36	3/4	1800
108052.00	12.82	10.76	4.85	24	3/4	1800
CATALOG No.	"C"	"L"	"AD"	VOLTS	H.P.	RPM

			TOLERANCES UNLESS SPECIFIED				DRAWN IPG 4/2/08	
03	ADDED NOTE ABOUT FAN GUARD FLAT LOCATION. ISAAC 09-4813	IPG 12/9/2009	DEC	INCHES			CHK BC 4/2/08	
02	ADDED DATA FOR 108605.00, 109101.00 & 109102.00	IPG 4/6/2009	SK	.XX ±.03	APPR			
01	ADDED PLUG CAP TO FAN GUARD. 108052.00	RPB 3/5/2009	RWS	XXX ±.005	TITLE OUTLINE			
	RELEASED: REF. 031879 & 031187	IPG 4/8/2008	BC	XXX ±.0005	48 FRAME DC - S56C MOUNT			
NO	REVISION	BY & DATE	CHK	ANG ±1/2°	MATL			
	THIRD ANGLE PROJECTION		RFP	PREV	FINISH			
				NETWORK FILE NAME	SIZE	DRAWING NO	REV	
					B	031891	03	