



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
  2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
  3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	AG	BS	2F	MOUNTING
575	182T	5.50	16.68	11.75	2.25	--	F1 OR F2
675	182T	6.50	17.68	12.75	2.75	5.50	F1 OR F2
675	184T	6.50	17.68	12.75	2.75	5.50	F1 OR F2

NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN BLR 05-01-1997		
						DEC.	INCHES				
4	REVISED TABLE - MOUNTING " F1 OR F2 "	RJW 07-25-2007	ML	.X	±.1				CHK ML 05-05-1997		
3	ADDED -675 W/182T FR. AND MTG. CN27400-320	CAE 12-07-1999		.XX	±.03				APPD GK 05-05-1997		
2	REV. Ø.41/.46 WAS 4 HOLES CN26000-635	MRB 06-26-1989		.XXX	±.005			TITLE OUTLINE	SCALE .3125=1		
1	NEW DRAWING CN24224	BLR 05-05-1997		.XXXX	±.0005			180T FR. - BB - TS - C'FACE	REF		
								MAT'L REF. B-SS68429-REV.2	FMF		
								FINISH	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP 05-05-1997	CAD FILE ss68429	SIZE B	DRAWING NO. SS68429	PAGE OF 4	REV.
						DIST LB					