



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	BS	2F
1550	404T	15.00	32.51	6.12	12.25
1700	405T	16.50	34.01	6.88	13.75

REVISION		BY & DATE		CHK		ANG		±7'30"		FINISH		DRAWN		CHK		APPR		SCALE		REF		FMF		PAGE		OF	
11	ADDED F2 VIEW	TJW	1/6/2010	CTO	DEC	INCHES				TITLE		OUTLINE		DRAWN		TJB		2/24/1988		REF		FMF		PAGE		OF	
10	REDRAWN IN AUTOCAD	TAT	6/29/2004	ML	X	±.1				TITLE		400T FR. - DR.PR. - (STD0		CHK		JL		2/24/1988		REF		FMF		PAGE		OF	
9	REPLACED ONE EYEBOLT WITH TWO CN28063	BJW	2/10/2000	XX		±.03				TITLE		400T FR. - DR.PR. - (STD0		APPR		ML		2/24/1988		REF		FMF		PAGE		OF	
8	UPDATED C'BOX GEOMETRY CN28063	TRB	2/10/2000	XXX		±.005				TITLE		400T FR. - DR.PR. - (STD0		APPR		ML		2/24/1988		REF		FMF		PAGE		OF	
7	REDRAWN ON CADD	TLB	2/24/1988	XXXX		±.0005				TITLE		400T FR. - DR.PR. - (STD0		APPR		ML		2/24/1988		REF		FMF		PAGE		OF	
NO										FINISH		PREV		RFP		NETWORK FILE NAME		SS509599		SIZE		DRAWING NO		REV			

