



| | | |
|--|---|--|
| UNITS: INCHES | | NOTES: 1. MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS 2. STANDARD PRODUCT USES BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE. 3. KEY DIMENSIONS EQUAL 0.500"x 0.500"x 3.88" (MOTOR SUPPLIED WITH KEY) |
| ROTATION FROM NDE | | |
| <div><div></div><div><input checked="" type="checkbox"/> CCW</div></div> | <div><div></div><div><input type="checkbox"/> CW</div></div> | |

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE ☐ PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED ☒ CERTIFIED

| | | | |
|---|---|--|--|
| <p>TOSHIBA</p> <p>www.toshiba.com/tic</p> <p>TOSHIBA INTERNATIONAL CORPORATION</p> | <p>PETRO-CHEMICAL DUTY</p> <p>EQP Global 841</p> | <p>TOTALLY ENCLOSED FAN COOLED</p> <p>FOOTED C-FACED</p> <p>3 PHASE INDUCTION MOTOR</p> <p>324TC-326TC F1 ASSEMBLY</p> | <p>DRAWING #: MDSLVO85-06</p> <p>REV. DATE: 07/11/18 REV. #: 2 PER.: M. O'DOWD</p> <p>REV. DESCRIP.: _____</p> |
| | | | |
| | | | |