



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1275	284T	11.75 [298.45]	24.44 [620.78]	---	9.50 [241.30]	4.75 [120.65]
1325	284T/286T	12.62 [320.55]	24.94 [633.48]	9.50 [241.30]	11.00 [279.40]	5.50 [139.70]
1512	286T	14.50 [368.30]	26.81 [680.97]	11.00 [279.40]	---	6.44 [163.58]

DRAWING REVISION	REVISION BY	DATE
C	J. OTTO	06-28-2016
ECO	T. BROWN	06-29-2016

APPROVED BY T. BROWN

DATE 06-29-2016

ECO DESCRIPTION

UPDATED TITLE BLOCK

COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

TOLERANCES UNLESS OTHERWISE SPECIFIED:

DEC.	INCH	mm	ANGLE
.X	\pm 0.1	[\pm 2.5]	\pm 7' 30"
.XX	\pm 0.03	[\pm 0.76]	
.XXX	\pm 0.005	[\pm 0.127]	
.XXXX	\pm 0.0005	[\pm 0.0127]	

REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [0.076/.381] X 45°

CORNER FILLETS: R.02 [51]

MACHINED SURFACES: 200 INCH/mm 5.1

mm SHOWN IN [BRACKETS]

DRAWN BY	DATE
RJW	10-08-2007
APPROVED BY	DATE
BW	10-09-2007
REFERENCE	
THIRD ANGLE PROJECTION	

REGAL™ Regal Beloit America, Inc.

DESCRIPTION: **OUTLINE**
280T FR. - DR. PR. - CAST IRON

MATERIAL: _____ PROCESS/FINISH: _____

SIZE: **B** DRAWING NUMBER: **SS207936** SHEET: **1 OF 1**