



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

DASH	FRAME	B	C	2F	BS
1850	444T	18.00	41.25	14.50	7.25
2050	445T	20.00	43.25	16.50	8.25

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN HLB 02-18-2002						
		DEC.	INCHES		CHK	DRS 02-18-2002					
		.X	±.1	TITLE OUTLINE 440T FR. - EXP. PR.	APPD	DJK 02-18-2002					
3	ADDED F2 VIEW	ML	.XX ±.03		SCALE	5=32					
2	UPDATED EYEBOLTS TO 2 WAS 1	ML	.XXX ±.005		REF						
1	NEW DRAWING	HLB	02-18-2002	DJK	.XXXX ±.0005	MAT'L					
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	SS518995	SIZE	DRAWING NO.	PAGE	OF	REV.
				DIST	WA		B	SS518995			3