

## SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN BOTH ENDBELLS & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

MAXIMUM FACE RUNOUT .004 T.I.R.
MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

'/	· · · · · · · · · · · · · · · · · · ·							* *				
				TOL UNLES	ERANCES S SPECIFIED	25		<del>И</del>		DRAWN	VS 01/23	3/08
				DEC.	INCHES	]		-	СНК	LST 01/2	3/08	
				.X	±.1					APPD		
				.xx	±.03	TITLE	TENNY DIOID "O"			SCALE	3=8	
				.xxx	±.005					REF	03496	,5
01	ADDED DRAIN SCREWS PER ECR-0034519	ARV 2/11/13	SK	.xxxx	±.0005	MAT'L. WASHGUARD			FMF			
NO.	REVISION	BY & DATE	СНК	ANG	±1/2°	FINISH				PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT — DO NOT SCALE THIS PRINT						CAD FILE	0L129042	SIZE	DRAWING NO	).		REV.
				DIST				Α	OL12904		42	01