


- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

2117	444T	41.58	--	18.00	14.50			14.62
2317	445T	43.58	--	20.00	16.50	14.50	14.50	16.64
2667	447T	47.08	--	23.50	20.00	16.50	16.50	20.14
3167	449T	52.08	--	28.50	25.00	20.00	20.00	25.14
DASH	FRAME	C	AG	B	2F	2FF	2FFF	BS

7	CORRECTED NEMA DIMENSIONS	CN09-1257	TJW	4/15/2009	CTO	TO TOLERANCES UNLESS SPECIFIED		DRAWN	MSG 09-19-2001			
6	REDRAWN IN SOLIDWORKS		RWR	2/19/2009	TB	DEC. INCHES		CHK	ML 09-21-2001			
5	REPLACED BLOWER SHROUD PER ISAAC 08-5529		MSG	01-08-2008	MSG	.X ±.1	APPD	HNH 08-24-2001				
4	CORRECTED C'BOX PER MU60939		CTO	09-09-2004	HNH	.XX ±.03	TITLE	SCALE 1=6				
3	ADDED DRAIN PLUG PER BRACKET CHANGE	CN 37358	MSG	05-07-2004	ML	.XXX ±.005	OUTLINE NEMA MOTORS 440T TEFC UEI					
2	DRAWING REPLACES 3XSF126FSSK-1	CN 34258	TJB	10-01-2001		.XXX ±.0005	MAT'L	REF				
NO.	REVISION		BY & DATE		CHK	ANG ±7'30"	FINISH	FMF				
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE	PREV				
						DIST BY		SIZE	DRAWING NO.	PAGE	OF	REV.
								B	XK2F1SS1			7