



(1) 1/2-14 NPT (PLUGGED)

(4) 3/8-16 UNC - 2B X .56 [14.22] DEEP ON A Ø5.875 [149.225] B.C.

MAXIMUM FACE RUNOUT TO BE .004 [.0102] T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 [.0102] T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 [.0508] T.I.R.

NOTE:-
 1) ALL-STAINLESS.
 2) VITON O-RINGS IN ENDBELL RABBETS.
 3) VITON SHAFT SEAL.
 4) BREATHER PLUGS IN L.E ENDBELL.
 5) ALL STAINLESS STEEL CONSTRUCTION.

DASH NO.	"C"	"AD"
750	11.70 [297.18]	6.13 [155.70]
800	12.20 [309.88]	6.63 [168.40]
850	12.70 [322.58]	7.13 [181.10]
900	13.20 [335.28]	7.63 [193.80]

DRAWING REVISION	REVISION BY	DATE
C	A.SUPPANAVAR	01/23/2018
ECO-0143018	APPROVED BY PK	DATE 04/11/2018

ECO DESCRIPTION
OUTLINE CONVERSION PROJECT
 COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.
 PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

TOLERANCES UNLESS OTHERWISE SPECIFIED:			
DEC.	INCH	mm	ANGLE
.X	±0.1	[±2.5]	±0.5°
.XX	±0.03	[±0.76]	
.XXX	±0.005	[±0.127]	
.XXXX	±0.0005	[±0.0127]	

REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [.076/.381] X 45°
 CORNER FILLETS: R.02 [.51]
 MACHINED SURFACES: 125 INCH 3.2 mm

DRAWN BY	DATE
LST	11/23/04
APPROVED BY	DATE
KH	11/23/04
REFERENCE	THIRD ANGLE PROJECTION
034896	

REGAL™ Regal Beloit America, Inc.	
DESCRIPTION	OUTLINE 56H FRAME TENV-RIGID "C"
MATERIAL	PROCESS/FINISH
SIZE B	DRAWING NUMBER 028661
SHEET 1 OF 1	