

# Product Information Packet

November 9, 2016

Data shown is for the current revision model #. Ensure your nameplate model # matches.

<b>Model Number:</b>	<b>5KS447LAA208D2</b>
<b>Catalog Number:</b>	<b>M7942</b>
<b>Instruction Manual:</b>	GEI-56128
<b>Connection Diagram:</b>	GEM2034E-FIG7
<b>Outline Drawing:</b>	239CC800AA

Accessory Connection Diagrams			
<b>Bearing Thermocouple:</b>	None	<b>Heater:</b>	None
<b>RTD:</b>	None	<b>Thermistor:</b>	None
<b>Thermostat:</b>	None	<b>Winding Thermocouple:</b>	None
<b>Bearing RTD:</b>	None		

Table of Contents	
Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04



**Marks:**

<b>MODEL NUMBER:</b>	<b>5KS447LAA208D2</b>	<b>Estimated Weight:</b>	2590 Lbs
<b>Outline Drawing:</b>	239CC800AA	<b>Time Rating:</b>	CONT
<b>Connection Diagram:</b>	GEM2034E-FIG7	<b>Enclosure:</b>	TEFC
<b>Instruction Book:</b>	GEI-56128	<b>Encl Construction:</b>	SD
<b>Design Code:</b>	49BD1169A	<b>Ambient Max(°C):</b>	40
<b>Type:</b>	KS	<b>Alt Ambient Max(°C):</b>	--
<b>Frame:</b>	447T	<b>Insulation Class:</b>	F
<b>Phases:</b>	3	<b>NEMA Design:</b>	A
<b>Poles:</b>	4	<b>Nominal Efficiency:</b>	96.2 %
<b>Output Power:</b>	200HP 148KW	<b>Guaranteed Efficiency:</b>	95.4
<b>RPM:</b>	1790	<b>3/4 Load Efficiency:</b>	96.5
<b>Voltage:</b>	460	<b>KVA Code:</b>	H
<b>Hertz:</b>	60	<b>Max KVAR:</b>	60.1
<b>Amps - FL:</b>	228.0	<b>Power Factor:</b>	85.5
<b>Service Factor:</b>	1.15	<b>Bearing - DE:</b>	6318ZC3S0
<b>Alt Service Factor:</b>	--	<b>Bearing - ODE:</b>	6318ZC3S0

**Enclosure is Totally Enclosed Fan-Cooled**

---

**Stamped Nameplate Notes:**

INVERTER DUTY PER NEMA MG1 PART 31  
 ALTERNATE RATING FOR PWM CONTROL:  
 1.0 SF VAR TORQUE RANGE 0-60 HZ

**Additional Information:**

4P - T EXTN  
 700 CU IN - 3.00" NPT  
 OIL RESISTANT SLEEVING ON LEADS  
 F1 MOUNTING  
 VIBRATION LIMIT 0.15 INCH PER SEC

**Performance Characteristics**

1st Winding 1st Connection

**Design: 49BD1169A**

**Marks:**


LOAD %	125.0	115.0	100.0	75.0	50.0	25.0	0.0
% EFF	95.82	96.01	96.45	96.49	96.33	94.69	0.00
% PF	87.23	86.74	85.55	81.55	72.24	49.57	2.58
AMPS	279.96	258.49	226.87	178.41	134.49	99.7	83.6

<b>TORQ(FL)#FT</b>	586.19	<b>TORQ(LR)%FL</b>	144.28	<b>TORQ(BD)%FL</b>	303.57
<b>AMPS(LR)</b>	1611.71	<b>PF AT START</b>	0.25		

This motor is capable of two cold or one hot start with a maximum connected load inertia of 3918 Lb-Ft Sq (164.95 Kg-meter Sq)at 100% voltage, where the load torque varies with the square of the speed. Acceleration time with maximum inertia and the above load type is 38 seconds. Safe stall time at 100% voltage is 118 seconds cold, 59 seconds hot. Rotor inertia is 89 Lb-Ft Sq (3.75 Kg-meter Sq).


<b>Open Circuit A-C:</b>	1.419	<b>Short Circuit D-C:</b>	0.026
<b>Short Circuit A-C:</b>	0.066	<b>X/R Ratio:</b>	9.698
<b>Stator Slots:</b>	72	<b>Rotor Slots:</b>	58

**Speed Torque Current Curve (First Connection, First Speed)**



NAME:501352727 OBJECT:239CC800AA DATE:31-Jul-07 14:14:01

Marks:



- NOTES:
1. CONDUIT BOX MAY BE PLACED WITH THE ENTRANCE DOWN, UP OR ON EITHER SIDE.
  2. F-1 ASSEMBLY AS SHOWN.
  3. F-2 ASSEMBLY CONDUIT BOX ON OPPOSITE SIDE.
  4. BRACKETED DIMENSIONS ARE METRIC (MILLIMETERS).

REV.	DESCRIPTION	DATE	APPROVED

SIGNATURES	DATE	GENERAL ELECTRIC COMPANY
DESIGNED BY: SAJAN 01/21/07	01/21/07	Fort Wayne, Indiana
DRAWN BY: SAJAN 01/21/07	01/21/07	
APPLIED PRACTICES		<b>OUTLINE</b> 447/449 T TEFC ESP 700 CU. IN. CONDUIT BOX <b>239CC800AA</b>
SCALE: 0.180 REF. NO.:		
SHEET NO. 1		DISTRIBUTION: MMP

Marks:

**Connection Diagram**  
**GEM2034E-FIG7**

