

PE145JP-2-2


CLOSE COUPLED PUMP MOTORS

NEMA PREMIUM EFFICIENCY

THREE PHASE, TOTALLY ENCLOSED FAN COOLED, JP FRAME

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
2	3600	145JP	7.00	6.20	20.30	3.50	0.50	0.34	1.40	2.75	5.50	4.00	5.00	7.10	6.95	0.00	2.75

FLANGE								Shaft Extension, Key Set									
AK	AJ	AH	BB	BC	BD	N*BF	U	R	S	EQ	ER	ES	ET	EP	EL	EM	EN
4.500	5.88	7.343	0.156	0.12	6.62	4*3/8-16	0.8745	0.771	0.190	1.578	7.31	1.65	5.952	1.18	1.156	1.0000	3/8-16
4.497		7.281	0.125				0.8740	0.756	0.188	1.548			5.922		1.154	0.9995	

Conduit Box		Bearings		Mount
AA	AB	DE	ODE	
0.75	6.10	6206-ZZ	6205-ZZ	

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease.





PE145JP-2-2

CLOSE COUPLED PUMP MOTORS

NEMA PREMIUM EFFICIENCY

THREE PHASE, TOTALLY ENCLOSED FAN COOLED, JP FRAME

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31








Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
2	3510	145JP	208-230/460	60	1.15	F	B	2.5	L	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %				
2.7	25.0	85.5	83.0	80.0	82.5	0.820	0.740	0.620	3.0	190	285	6206-ZZ	6205-ZZ	9 Lead 2Y/Y	49

NAME PLATE

 North American Electric, Inc.													CONNECTION DIAGRAMS 208-230V 										
INVERTER DUTY 20:1 VT; 10:1 CT					CLOSE COUPLED PUMP MOTOR																		
CAT NO:		PE145JP-2-2			FRAME		145JP		PHASE		3		460V 										
HZ		60		S.F.		1.15		HZ		50		S.F.				1.0		ENCL		TEFC		IP	
HP		2		RPM		3510		HP		2		RPM		2870		DUTY		CONT		DES		B	
VOLTS				208-230/460				VOLTS				190/380				AMB		40° C		INS		F	
FLA		5.8 - 5.3 / 2.65				FLA		6.4/3.2				DE BEARING				6206-ZZ							
CODE		L		P.F.		0.82		CODE		F		P.F.		0.86		ODE BEARING				6205-ZZ			
EFF		85.5		MIN		82.5		EFF		83.5		MIN		80.5		LUB: Mobil Polyrex EM							
MOTOR WEIGHT			49			LBS			CONNECTION			9 Lead 2Y/Y			SER NO								
Specifically designed for use on industrial and commercial pumping units. Hernando, Mississippi																CC 082A							

APPLICATIONS:

Specifically designed for use on industrial and commercial pumping units.