



# WORLDWIDE ELECTRIC MOTOR DATA SHEET

## WWE15-36-215JP



HORSEPOWER	15		
RPM / POLES	3600 / 2		
VOLTAGE / PHASE	230 / 460 V / 3		
FRAME	215JP		
ENCLOSURE / DEGREE OF PROTECTION	TEFC / IP54		
FREQUENCY	60 HZ Suitable For 50 HZ Operation With 1.0 SF		
FULL LOAD SPEED	3530 RPM		
SERVICE FACTOR	1.15		
INSULATION CLASS	F		
FULL LOAD AMPS; 230 / 460	33.4 / 16.7 A		
LOCKED ROTOR AMPS (STARTING); 230 / 460	232 / 116 A		
NO LOAD CURRENT	11.2 / 5.6 A		
NEMA CODE LETTER	G		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	100%	90.2%	0.86
	75%	90.5%	0.88
	50%	90.7%	0.81
DUTY CYCLE	CONTINUOUS		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	22.5 lb.ft.	230%	380%
SLIP	2.01%		
NEMA DESIGN	B		
MOMENT OF INERTIA	0.346 lb.ft. <sup>2</sup>		
MAX. TIME LOCKED ROTOR (Hot)	20 Seconds		
MAX. AMBIENT TEMPERATURE	40° C		
MAX. ELEVATION	3300 Ft. Above Sea Level		
TEMPERATURE RISE (At Full Load)	80° C		
DE BEARING	6309ZZ		
ODE BEARING	6306ZZ		
REGREASING INT. - DE BEARING	---		
REGREASING INT. - ODE BEARING	---		
GREASE TYPE	Mobil Polyrex EM		
MOUNTING	F1 (F2 Suitable)		
ROTATION	Bi-Directional		
SHAFT MATERIAL	1045 Carbon Steel		
CONNECTION DIAGRAM	230 / 460 V - 9 Lead Δ		
APPROXIMATE WEIGHT	186 Lbs.		




CC006A





# WORLDWIDE ELECTRIC MOTOR DRAWING

## WWE-215JP



**DIMENSIONS - INCHES**

MOUNTING					A	B	C	D	G	J	P	L	AH	AB	EQ	AA
E	2F1	2F2	H	BA												
4.25	5.5	7	0.41	4.25	10.5	9	25.866	5.25	0.709	2.36	10.63	12.4	8.125	8.63	2.375	1

KEY		KEYSET	U	FLANGE				ET	EM	EL	EP	ER	EN	
WIDTH	LENGTH	R		AK	AJ	BF	BB							BD
0.252	2.6	1.112	1.250	8.5	7.25	1/2-13	0.256	8.9	5.875	1.375	1.75	1.772	8.37	1/2-13