



WORLDWIDE ELECTRIC MOTOR DATA SHEET

**FARM5-18-184T**



HORSEPOWER	5		
RPM / POLES	1800 / 4		
VOLTAGE / PHASE	230 V / 1		
FRAME	184T		
ENCLOSURE / DEGREE OF PROTECTION	TEFC / IP55		
FREQUENCY	60 HZ		
FULL LOAD SPEED	1720 RPM		
SERVICE FACTOR	1.15		
INSULATION CLASS	F		
FULL LOAD AMPS	21.2 A		
LOCKED ROTOR AMPS (STARTING)	160 A		
NO LOAD CURRENT	6.6 A		
NEMA CODE LETTER	J		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	100%	81.0%	0.90
DUTY CYCLE	CONTINUOUS		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	15.3 lb.ft.	380%	240%
SLIP	4.44%		
NEMA DESIGN	L		
MOMENT OF INERTIA	0.81 lb.ft. <sup>2</sup>		
MAX. TIME LOCKED ROTOR (Hot)	20 Seconds		
MAX. AMBIENT TEMPERATURE	40° C		
MAX. ELEVATION	3300 Ft. Above Sea Level		
TEMPERATURE RISE (At Full Load)	80° C		
BASE TYPE	Rigid Base		
DE BEARING	6206ZZ		
ODE BEARING	6206ZZ		
REGREASING INT. - DE BEARING	---		
REGREASING INT. - ODE BEARING	---		
GREASE TYPE	Mobil Polyrex EM		
MOUNTING	F1		
ROTATION	Bi-Directional		
SHAFT MATERIAL	1045 Carbon Steel		
CONNECTION DIAGRAM	230 V - 6 Lead		
APPROXIMATE WEIGHT	105 lbs.		
REPLACEMENT PARTS	Capacitor (Start)	SCFARM5 (500µF/300V)	
	Capacitor (Run)	RCFARM5 (50µF/450V)	
	Endbell (DE)	FEBELLFARM180	
	Endbell (ODE)	REBELLFARM180	
	Fan	FAN184aTEFC	
	Fan Cover	FCOVERFARM180	
	Junction Box	JBXFARM180	
	Overload (Manual)	PROFARM5	
	Switch (Centrifugal)	CSWITCHFARM5	





# WORLDWIDE ELECTRIC MOTOR DRAWING

## FARM5-18-184T

