



**WORLDWIDE ELECTRIC MOTOR DATA SHEET**

**EP30-12-326T**



HORSEPOWER	<b>30</b>		
RPM / POLES	<b>1200 / 6</b>		
VOLTAGE / PHASE	<b>230 / 460 V / 3</b>		
FRAME	<b>326T</b>		
ENCLOSURE / DEGREE OF PROTECTION	<b>TEFC / IP55</b>		
FREQUENCY	<b>60 HZ Suitable For 50 HZ Operation With 1.0 SF</b>		
FULL LOAD SPEED	<b>1185 RPM</b>		
SERVICE FACTOR	<b>1.25 SF at 40° C / 1.0 SF at 55° C</b>		
INSULATION CLASS	<b>F</b>		
FULL LOAD AMPS; 230 / 460	<b>77.6 / 38.8 A</b>		
LOCKED ROTOR AMPS (STARTING); 230 / 460	<b>435 / 218 A</b>		
NO LOAD CURRENT	<b>37.0 / 18.5 A</b>		
NEMA CODE LETTER	<b>G</b>		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	<b>100%</b>	<b>93.0%</b>	<b>0.78</b>
	<b>75%</b>	<b>92.0%</b>	<b>0.73</b>
	<b>50%</b>	<b>89.6%</b>	<b>0.71</b>
DUTY CYCLE	<b>S1 / Continuous</b>		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	<b>133.0 lb.ft.</b>	<b>210%</b>	<b>260%</b>
SLIP	<b>1.25%</b>		
NEMA DESIGN	<b>B</b>		
MOMENT OF INERTIA	<b>12.941 lb.ft.<sup>2</sup></b>		
NUMBER OF STARTS (Hot / Cold)	<b>2 Hot / 3 Cold</b>		
MAX. AMBIENT TEMPERATURE	<b>40° C at 1.25 SF / 55° C at 1.0 SF</b>		
MAX. ELEVATION	<b>3300 Ft. Above Sea Level</b>		
TEMPERATURE RISE (At Full Load)	<b>80° C</b>		
DE BEARING	<b>6312</b>		
ODE BEARING	<b>6312</b>		
GREASE TYPE	<b>Mobil Polyrex EM</b>		
MOUNTING	<b>F1 (F2 Suitable)</b>		
ROTATION	<b>Bi-Directional</b>		
APPROXIMATE WEIGHT	<b>660 lbs.</b>		
AREA CLASSIFICATION	<b>Class I, Division 2, Groups A, B, C, D</b>		
TEMPERATURE CODE AT 40°C AMBIENT	<b>T3C</b>		
TEMPERATURE CODE AT 55°C AMBIENT	<b>T3A</b>		
INVERTER RATING	<b>10:1 CT / 20:1 VT PWM Type</b>		
SPECIFICATION - In Accordance With	<b>NEMA, CSA</b>		



**CC067A**





# WORLDWIDE ELECTRIC MOTOR DRAWING

## EP-326T



DIMENSIONS - INCHES

MOUNTING					A	B	C	D	G	J	P	L	AB
E	2F1	2F2	H	BA									
6.25	10.5	12	0.66	5.25	15.3	14	30.9	8	0.984	2.76	17.75	18.25	14.17

KEY		KEYSET	SHAFT		TERMINAL BOX				
S	ES	R	N-W	U	AA	XB	XC	XD	XE
0.5	3.91	1.845	5.25	2.125	3	2.6	10.55	8.98	10.47