



4X MOUNTING SLOT
.34[8.6] X 1.22[30.9]

6X TORQ-SLTD HEAD SELF
TAPPING SCREWS (189156-01)
TORQUE TO 30 INCH/LBS.

CAUTION
BASE TO BE ATTACHED WITH
SCREWS. DO NOT WELD.

3/16 X 3/16 X
1.38[35.0]
LONG KEY

4X 3/8-16 UNC-2B
ON A ϕ 5.875[ϕ 73.02] B.C.

NOTES:

- 1. PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .004[.10] T.I.R.
- 2. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004[.10] T.I.R.
- 3. SHAFT RUNOUT NOT TO EXCEED .002[.05] T.I.R.
- 4. END PLAY NOT TO EXCEED .010[.25] MEASURED WITHIN NO THRUST.
- 5. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS.

● = CRITICAL DIMENSION

DRAWING REVISION H ECO-0097387 ECO DESCRIPTION SEP ECO	REVISION BY A.A. BAUGHMAN A.A. BAUGHMAN	DATE 04-19-2016 04-19-2016	TOLERANCES UNLESS OTHERWISE SPECIFIED DIM: INCH mm ANGLE X ±0.1 ±2.51 ±0.5° XX ±0.02 ±0.511 XXX ±0.005 ±0.1271 XXXX ±0.0005 ±0.01271	DRAWN BY DH	DATE 02-23-2000	DESCRIPTION MODEL-CFHP-56FR OUTLINE
<small>COPYRIGHT REGAL BELLOIT AMERICA, INC. ALL RIGHTS RESERVED. REGAL BELLOIT AMERICA, INC. (PARENT) AND COMPANY OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER ENTITY IS FORBIDDEN BY RECEIVING IT TO ADAPT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small>			<small>REMOVE BURRS & BREAK SHARP EDGES .0031.015 (1.076/381) CORNER FILLETS .02 (5.1) MACHINED SURFACES ±.001 INCH/mm ±.025 mm SHOWN IN [BRACKETS]</small>	APPROVED BY:	DATE:	PROCESS/FINISH
			THIRD ANGLE PROJECTION	SIZE [DWG NO.]	C827	SHEET 1