



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

10	UPDATED WITH NEW FRAME PER ISAAC 09-5049	JJB 6/29/2010		TOLERANCES UNLESS SPECIFIED		DRAWN RM 06-19-1991
9	REV. FAN GUARD & C-DIM. PER CN39335	RWR 6/29/2010	DEC	INCHES		CHK TLB 06-28-1991
8	REDRAWN IN AUTOCAD	TAT 06/29/2004	ML	x ±.1	APPR ML 06-28-1991	
7	REVISED 'C' DIM. CN 26153	KL 01/22/1999	XX	xx ±.03	SCALE 1:6	
6	RE-ISSUE 'C' DIM. WAS 37.44 & 39.44	BLR 06/10/1997	XXX	xxx ±.005	REF 444/445TS FR. - TEFC - TFN	
5	UPDATED TO SHOW NEW FRAME AND LIFT LUGS CN21946	PGK 01/22/1997	XXXX	xxxx ±.0005	MATL	FMF MU96082
NO	REVISION	BY & DATE	CHK ANG ±1/2°	FINISH	PREV	PAGE OF
			RFP	NETWORK FILE NAME	SS514022	SIZE DRAWING NO
						B SS514022
						REV 10

DASH	FRAME	B	C	2F	2FF	BS
2025	444/445TS	19.75	39.62	14.50	16.50	8.25

