



NAMEPLATE DATA		EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: B384 CUST PN: 182678 HP: 5.0 SF: 1.15 ROT: CW RPM: 3450 TYPE: CP CODE: G FORM: KHH FRAME: R56Y VOLTS: 208-230 AMPS: 22.0 MAX AMPS: SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 40 DUTY: CONT ENCLOSURE: DP THERMALLY PROTECTED			1. TERMINAL BOX TO BE LOCATED AT 12:00 WITHIN +/- 1 1/2' 2. NAMEPLATE LOCATION AT 3:00 HORIZONTAL

ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. ALL OTHER DIMENSIONS ARE TOLERANCED PER THE FOLLOWING CHART UNLESS OTHERWISE SPECIFIED.

"C" DIM. = +/- .055[1.40]
 SHAFT EXT. = +/- .034[.86]
 LEAD LENGTHS = +/- 1.00[25.4]
 EXTENDED THRU-BOLTS = +/- .050[1.27]
 ANGULAR DIM. = +/- 2 DEG.

● = CRITICAL DIM.

PERFORMANCE CURVE		APPROVED SAMPLE	
UL COMPONENT		CSA	
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER		DISTRIBUTION	

DRAWING REVISION D ECO-0159053 SEE ECO	REVISION BY NANCY.LIU APPROVED BY KEFU.SHI	DATE 12-27-2018 12-27-2018	TOLERANCES UNLESS OTHERWISE SPECIFIED DEC. INCH mm ANGLE X ±0.1 [±0.5] ±0.5° .XX ±0.02 [±0.13] .XXX ±0.005 [±0.013] .XXXX ±0.0005 [±0.0013] REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.08/.38] CORNER FILLETS .02 [0.5] MACHINED SURFACES .125/ mm ^{3/2} mm SHOWN IN [BRACKETS]	DRAWN BY: BS DATE: 08-10-2009 APPROVED BY: LX DATE: 08-10-2009 REFERENCE	Regal Beloit America, Inc. DESCRIPTION MODEL-CFHP-56FR OUTLINE MATERIAL PROCESS/FINISH	SIZE DWG NO C B384 SHEET 1
---	---	----------------------------------	---	--	---	-------------------------------------