Uncontrolled Copy 4 ø6.47 [ø164.3] TOP OF WARNING -STICKER 11.84 [300.74] 5.72 [145.29] 2.00 ---[50.8] SHAFT EXT. 1.97 [50.04] 4.95 .12 [3.0] [127.73] 4.12 8.97 [227.84] [104.65] TOP OF MOTOR -NAMEPLATE 1.88 **-**--[47.75] USABLE EXT. 0 1/2-14 PIPE TAP— FOR CONDUIT CONNECTION (PLUGGED) 1.38 [35.1] KEY KEY .19[4.8] SQ. 6.75 [171.5] LENGTH ø.6250<sup>+.0005</sup> [ø15.875<sup>+.013</sup> [ø15.875<sup>+.000</sup>] 4.58 [116.33] 3.50<sup>+</sup>.00 -.06 BASE 88.9+.0 .12 [3.0] 3.00 [76.2] 2.75 1.56 [39.6] (2.44)[69.9] 6.38 [162.1] 1.00 [25.4] 1.22 [31.0] [8.6] 2.44 [62.0] 4.00 [101.6] SLB
DATE:
12-10-2009
APPROVED BY:
TCOLOMA
DATE:
12-10-2009
REFERENCE REGAL Regal Beloit America, Inc. ANGLE ±0.5 OUTLINE THIRD ANGLE PROJECTION SIZE DWG SHEET 1 RS1074AL 4