



NAMEPLATE DATA		EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: C48J2DB11 CUST PN: T1052 HP: 1/2 SF: 1.6 ROT: CCWPE RPM: 3450 TYPE: C CODE: L FORM: FRAME: 56J VOLTS: 230/115 AMPS: 4.3/8.6 MAX AMPS: 5.4/10.8 SF AMPS: PH: 1 HZ: 60 INS: B AMB: 40°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED			<ol style="list-style-type: none"> 1. FINISH PAINT TO BE SATIN BLACK. 2. .44[11.2] WRENCH FLATS ON SHAFT FOR ACCESS TO THIS WRENCH FLAT REMOVE END COVER. 3. STAINLESS STEEL SHAFT EXT. 4. LIMITS ON AMPLITUDE OF VIBRATION MEASURED AT BEARING HOUSING = .001[.03]. 5. CONNECT MOTOR FOR 230 VOLTS QUICK VOLTAGE CHANGE PLUG INCLUDED ON TERMINAL BOARD. VOLT STICKER TO READ THAT CONNECTED VOLTAJE.

PERFORMANCE CURVE		APPROVED SAMPLE	
C48J2W14			
UL COMPONENT		CSA	
FILE#	CCN#	FILE#	GUIDE#
-	-	LR43341	4211-01
CUSTOMER		DISTRIBUTION SERVICES	

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:	REGAL™ Regal Beloit America, Inc.
C	R.LIAN	09-21-2016	DEC. INCH mm ANGLE	Brain.Z	
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°	DATE:	DESCRIPTION
ECO-0109281	Q.HE	09-21-2016	.XX ±0.02 [±0.51]	10-05-2010	
ECO DESCRIPTION			.XXX ±0.005 [±0.127]	APPROVED BY:	OUTLINE
SEE ECO			.XXXX ±0.0005 [±0.0127]	sara	
			REMOVE BURRS & BREAK SHARP EDGES .003[.015] [0.076/.381]	DATE:	PROCESS/FINISH
			CORNER FILLETS .02 [L51]	10-05-2010	
			MACHINED SURFACES 125/3.2	REFERENCE	SIZE DWG NO
			mm SHOWN IN [BRACKETS]	-	
				THIRD ANGLE PROJECTION	T1052
					1