



NOTES:

1. PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .004 T.I.R.
2. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004 T.I.R.
3. SHAFT RUNOUT NOT TO EXCEED .002 T.I.R.
4. FOR THREADED SHAFT EXT. MATING PARTS SHOULD BE RELIEVED ONE THREAD TO CLEAR FILLET
5. FOR THREADED SHAFT EXT. ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004 TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR.
6. END PLAY NOT TO EXCEED .010 MEASURED WITH NO THRUST

DRAWING REVISION A	REVISION BY G.ALVIDREZ	DATE 04-30-2015	TOLERANCES UNLESS OTHERWISE SPECIFIED			DRAWN BY: G.ALVIDREZ	Regal Beloit America, Inc.
ECO 0067917	APPROVED BY G.ALVIDREZ	DATE 04-30-2015	DEC.	INCH	mm	ANGLE	
ECO DESCRIPTION SEE ECO			.X	±0.1	±2.5	±0.5°	APPROVED BY:
			.XX	±0.02	±0.51		DATE:
			.XXX	±0.005	±0.127		REFERENCE
			.XXXX	±0.0005	±0.0127		MATERIAL
COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [.076/.381] CORNER FILLETS .02 [1.51] MACHINED SURFACES $\sqrt{125}$ INCH/mm $\sqrt{3.2}$ mm SHOWN IN [BRACKETS]			DESCRIPTION MODEL-CFHP-56FR OUTLINE	PROCESS/FINISH
						THIRD ANGLE PROJECTION	SIZE DWG NO C H629
							SHEET 1