



TECHNICAL INFORMATION

1. BEARING LUBRICATION DE: TURBINE OIL ISO VG32
ODE: TURBINE OIL ISO VG32
2. BEARING TYPE DE: M9-90 INS
ODE: M9-90 INS
3. WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(Pt0°C-100ohm)
LOCATION: IN STATOR SLOT
4. BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
5. SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 300
6. ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS UNI DIRECTIONAL
7. MOTOR PAINT COLOR: GRAY
8. APPROX. WEIGHT: 7000 Lbs
9. ACCESORIES:

UNITS: INCHES

DRAWING LIST		MOTOR OUTLINE FOR THREE PHASE INDUCTION MOTOR					
MAIN TERMINAL BOX 130-7622-55		CUSTOMER NAME		P.O. NO.		MOTOR TAG NO.	
AUX TERMINAL BOX FOR		OUTPUT HP	POLE	VOLTAGE V	FREQUENCY Hz	FULL LOAD SPEED (min ⁻¹)	
SPACE HEATER	130-7520-50	TYPE	FORM	INS. CLASS F	RATING CONT.	FRAME 5811USS	TOSHIBA MODEL NO. S.F. ENCLOSURE TEFC
R.T.D.	130-7522-51	TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.					
THERMISTOR	N/A	3rd ANGLE PROJ.	PREPARED BY: B SIDLE	DATE: 7/7/08	CHECKED BY: S JOHNSON	DATE: 2/10/09	DRAWING NO.: MDSL0071-22
PRODUCTION #	N/A	NO. REVISION		BY	DATE	REV. 1	