



TECHNICAL INFORMATION

- BEARING LUBRICATION DE: MOBIL POLYREX EM
ODE: MOBIL POLYREX EM
- BEARING TYPE DE: 6315C3
ODE: 6315C3 INSULATED
- WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(Pt0°C-100ohm)
LOCATION: IN STATOR SLOT
- BEARING TEMP. DETECTORS
NUMBER AND TYPE: N/A
- SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 200
- ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS UNI DIRECTIONAL
- MOTOR PAINT COLOR: GRAY
- APPROX. WEIGHT: 7000 Lbs
- ACCESORIES:

UNITS: INCHES

DRAWING LIST		MOTOR OUTLINE FOR THREE PHASE INDUCTION MOTOR					
MAIN TERMINAL BOX 130-7622-55		CUSTOMER NAME		P.O. NO.		MOTOR TAG NO.	
AUX TERMINAL BOX FOR		OUTPUT HP	POLE	VOLTAGE V	FREQUENCY Hz	FULL LOAD SPEED (min ⁻¹)	TOSHIBA MODEL NO.
SPACE HEATER	130-7520-50	TYPE	FORM	INS. CLASS F	RATING CONT.	FRAME 5811USS	S.F. ENCLOSURE TEFC
R.T.D.	130-7522-51	TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.					
THERMISTOR	N/A	3rd ANGLE PROJ.	PREPARED BY: B SIDLE	DATE: 4/24/07	CHECKED BY: S Johnson	DATE: 4/26/07	DRAWING NO.: MDSL0071-17
PRODUCTION #	N/A	NO.	REVISION	BY	DATE		REV. 2
		2	GRS FROM SRI, ADD DOWELS JACKING TO INLINE	RWS	1/6/14		
		1	ADD AIR DEFLECTOR	BEN	12/15/08		
		0	FIRST ISSUE	BCS	4/24/07		