



TECHNICAL INFORMATION

1. BEARING LUBRICATION DE: MOBIL POLYREX EM
ODE: MOBIL POLYREX EM
2. BEARING TYPE DE: 6326C3
ODE: 6326C3 INSULATED
3. WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(Pt0°C-100ohm)
LOCATION: IN STATOR SLOT
4. BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
5. SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 400
6. ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS BI DIRECTIONAL
7. MOTOR PAINT COLOR: _____
8. APPROX. WEIGHT: 9100 Lbs
9. ACCESORIES: _____

DRAWING LIST

| | | | | | |
|---|-------------|-----|-----------------------------------|-----|---------|
| MAIN TERMINAL BOX 130-7532-02 | | 3 | GRS FROM SRI JACKING TO INLINE | RWS | 1/3/14 |
| AUX TERMINAL BOX FOR | | 2 | UPDATE | MH | 8/15/05 |
| SPACE HEATER | 130-7520-50 | 1 | UPDATE | RW | 4/16/03 |
| R.T.D. | 130-7522-51 | | | | |
| THERMISTOR | N/A | 0 | FIRST ISSUE | RW | 3/25/03 |
| PRODUCTION # | N/A | NO. | REVISION | BY | DATE |

**MOTOR OUTLINE FOR
THREE PHASE INDUCTION MOTOR**

| | | | | | | |
|--|----------------------------|-------------------|----------------------|---|------------------------------|--------------------|
| CUSTOMER NAME | | | | P.O. NO. | MOTOR TAG NO. | |
| OUTPUT HP | POLE 8 | VOLTAGE V | FREQUENCY Hz | FULL LOAD SPEED (min ⁻¹) | TOSHIBA MODEL NO. | |
| TYPE | FORM | INS. CLASS F | RATING CONT. | FRAME 5811/12 | S.F. | ENCLOSURE TEAAC |
| TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A. | | | | | | |
| 3rd ANGLE PROJ. | PREPARED BY: R. WILKINS | DATE: 03/25/03 | CHECKED BY: M. HO | DATE: 04/01/03 | DRAWING NO.: MDSL 0077-04 | REV. 3 |