



SPECIAL FEATURES:

- 1) DOUBLE LIP OIL SEALS BOTH ENDS.
- 2) GASKETS THROUGHOUT.
- 3) O-RING SEALED ENDBELLS & THRU BOLTS.
- 4) LOCKED BEARING W/SEALED LOCK SCREWS.

DASH NO.	"C"	"AD"
900	14.77	5.11
950	15.27	5.61

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN
		DEC.	INCHES			JJK 04/04/02
		.X	±.1			CHK
		.XX	±.03	TITLE		APPD
02	14.77 WAS 14.87, 15.27 WAS 15.37	.XXX	±.005	OUTLINE - 180TC FRAME		SCALE 1=2
01	ADDED HOLE PLUG PER ECO 03-617	.XXXX	±.0005	TEFC - RIGID "C"		REF OLG131167
NO. REVISION		CHK	ANG ±7'30"	MAT'L STAINLESS STEEL DUCK		FMF G131901.00
		BY & DATE		FINISH		PREV
		RFP		CAD FILE	035437ME	SIZE B
		DIST	NLV			DRAWING NO. 035437ME
						REV. 02

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED
 THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT