



TECHNICAL INFORMATION

1. BEARING LUBRICATION DE: TURBINE OIL ISO VG32
ODE: TURBINE OIL ISO VG32
2. BEARING TYPE DE: M11-125 INS
ODE: M11-125 INS
3. WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(Pt0C-100ohm)
LOCATION: IN STATOR SLOT
4. BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
5. SPACE HEATER _____ 1 PHASE
VOLTS: 120 WATTS: 800
6. ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS UNI DIRECTIONAL
7. MOTOR PAINT COLOR: GRAY
8. APPROX. WEIGHT: 14,000 Lbs
9. ACCESSORIES:

**PRELIMINARY
FOR QUOTATION ONLY
DO NOT BUILD
FROM THIS DRAWING**

DRAWING LIST

MAIN TERMINAL BOX	
130P-7550-68	
AUX TERMINAL BOX FOR	
SPACE HEATER	130-7520-50
R.T.D.	130-7522-51
THERMISTOR	N/A
PRODUCTION #	N/A

NO.	0	FIRST ISSUE	REVISION	BY	DATE
	1	CHANGE FOOT HOLE DIMENSION FROM $\phi 1.375''$		AF	6/27/2018

OUTPUT		CUSTOMER NAME		MOTOR TAG NO.	
HP	4	TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.		TOSHIBA MODEL NO.	
POLE	V	P.O. NO.		MOTOR TAG NO.	
FORM	F	INS. CLASS		FRAME	
TYPE	CONT.	RATING		S.F.	
		450-1600		ENCLOSURE	
				WP-II	

3rd ANGLE PROJ. PREPARED BY: R. QAO DATE: 08/28/12 CHECKED BY: DATE: DRAWING NO.: MDL0087-75 REV. 1

**MOTOR OUTLINE FOR
THREE PHASE INDUCTION MOTOR**

UNITS: INCHES