



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FR.	C	B	2F	BS	AG	2FF	FOOT HOLE	MOUNTING
575	182TC	16.19	5.75	4.50	2.25	11.00	----	4	F1 OR F2
675	182TC	17.19	6.75	4.50	2.75	12.00	5.50	8	F1 OR F2
675A	184TC	17.19	6.75	5.50	2.75	12.00	----	4	F1 OR F2
720	182TC	17.64	7.20	4.50	2.98	12.45	5.96	8	F1 OR F2
720	182TC	17.64	7.20	4.50	2.98	12.45	----	4	F1 ONLY
775	184TC	18.19	7.75	5.50	3.25	13.00	----	8	F1 OR F2
875	184TC	19.19	8.75	5.50	3.75	14.00	----	8	F1 OR F2
925	184TC	19.69	9.25	5.50	4.00	14.50	----	8	F1 OR F2

NO.		REVISION	BY & DATE	CHK	ANG	FINISH	TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN	
							DEC.	INCHES		ML	
							.X	±.03		03-26-2008	
							.XX	±.005		03-27-2008	
							.XXX	±.0005		03-27-2008	
							.XXXX	±.0005		03-27-2008	
										5-16	
										SS68967D	
										ME080077, MUB6314	
										ME080077	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT							RFP	6-20-2008	CAD FILE SS69914	SIZE	DRAWING NO. PAGE 1 OF 1 REV.
							DIST	LB	B	SS69914	