



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS311038)

						TOLERANCES UNLESS SPECIFIED				DRAWN KL 10-26-2000	
						DEC.	INCHES			CHK	DJK 10-27-2000
						.XX	±.03	TITLE OUTLINE - ENCODER PROV. 280T FR. - TEFC - TFPA - 11.00" LAM.		SCALE 1=4	
2 CORRECTED C'BOX HOLE NOTE CN29200-1454 HLB 02-16-2001						.XXX	±.005			REF	
1 NEW DRAWING MU34251 KL 10-30-2000						.XXXX	±.0005	MAT'L		FMF	
NO. REVISION						CHK	ANG	FINISH		PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE SS311075		SIZE	DRAWING NO.	PAGE OF
DASH	FRAME	B	C	2F	BS	DIST LB		B	SS311075	2	
1275	284T	11.50	28.58	9.50	4.75						
1425	286T	13.00	30.08	11.00	5.50						