



TECHNICAL INFORMATION

- BEARING LUBRICATION DE: CHEVRON SRI
ODE: CHEVRON SRI
- BEARING TYPE DE: 6315C3
ODE: 6315C3 INSULATED
- WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(PtO°C-100ohm)
LOCATION: IN STATOR SLOT
- BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
- SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 400
- ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS UNI DIRECTIONAL
- MOTOR PAINT COLOR: _____
- APPROX. WEIGHT: 7300 Lbs
- ACCESORIES: _____

DRAWING LIST				
MAIN TERMINAL BOX	130-7532-02			
AUX TERMINAL BOX FOR		2	UPDATE	MH 8/15/05
SPACE HEATER	130-7520-50			
R.T.D.	130-7522-51	1	UPDATE	RW 4/16/03
THERMISTOR	N/A			
		0	FIRST ISSUE	RW 3/25/03
PRODUCTION #	N/A	NO.	REVISION	BY DATE

**MOTOR OUTLINE FOR
THREE PHASE INDUCTION MOTOR**

CUSTOMER NAME				P.O. NO.	MOTOR TAG NO.
OUTPUT	POLE	VOLTAGE	FREQUENCY	FULL LOAD SPEED	TOSHIBA MODEL NO.
1250 HP	2	4000 V	60 Hz	3575 (min⁻¹)	M253WTAL11F-C
TYPE	FORM	INS. CLASS	RATING	FRAME	S.F.
TIKE	DCW	F	CONT.	5811/12	1.15
ENCLOSURE WP-II					
TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.					
3rd ANGLE PROJ.	PREPARED BY:	DATE:	CHECKED BY:	DATE:	DRAWING NO.:
	R.WILKINS	03/25/03	M. HO	04/01/03	MDSL 0087-01
					REV.
					2