



TECHNICAL INFORMATION

1. BEARING LUBRICATION DE: CHEVRON SRI
ODE: CHEVRON SRI
2. BEARING TYPE DE: 6315C3
ODE: 6315C3 INSULATED
3. WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(PtO°C-100ohm)
LOCATION: IN STATOR SLOT
4. BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
5. SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 400
6. ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS UNI DIRECTIONAL
7. MOTOR PAINT COLOR: _____
8. APPROX. WEIGHT: 7300 Lbs
9. ACCESSORIES: _____

DRAWING LIST				
MAIN TERMINAL BOX				
130-7532-02				
AUX TERMINAL BOX FOR	2	UPDATE	MH	8/15/05
SPACE HEATER 130-7520-50				
R.T.D. 130-7522-51	1	UPDATE	RW	4/16/03
THERMISTOR N/A				
	0	FIRST ISSUE	RW	3/25/03
PRODUCTION #	N/A	NO.	REVISION	BY DATE

MOTOR OUTLINE FOR THREE PHASE INDUCTION MOTOR

CUSTOMER NAME				P.O. NO.	MOTOR TAG NO.
OUTPUT	POLE	VOLTAGE	FREQUENCY	FULL LOAD SPEED	TOSHIBA MODEL NO.
800 HP	2	4000 V	60 Hz	3565 (min ⁻¹)	8003WTAL11F-A
TYPE	FORM	INS. CLASS	RATING	FRAME	S.F.
TIKK	DCW	F	CONT.	5811/12	1.15
ENCLOSURE WP-II					
TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.					
3rd ANGLE PROJ.	PREPARED BY:	DATE:	CHECKED BY:	DATE:	DRAWING NO.:
	R.WILKINS	03/25/03	M. HO	04/01/03	MDSL 0087-01
					REV. 2